

Accessories

Automatic Flushing Timer

- Provides flow-thru technology for steam- and reservoir-type humidifiers
- Automatically flushes the humidifier water pan with fresh, clean water every two hours
- Programmable to 10-, 20-, and 30-second flushes per cycle reduces or eliminates servicing during the humidification season
- Uses minimal electricity
- Reduces water usage by up to 98 percent when compared to conventional flow-thru humidifiers
- Quick and easy to install



Performance

FLUSH TIME	WATER USED PER FLUSH	WATER USED PER DAY
10-Second Flush	16 Ounces	1.5 Gallons
20-Second Flush	32 Ounces	3.0 Gallons
30-Second Flush	48 Ounces	4.5 Gallons

Above is based on laboratory tests conducted at Skuttle Mfg. Co., completed in August 2005.

NOTE

Factory setting is for 10-second flushing cycle every two hours.

NOTE

In areas where the domestic water supply contains excessive chlorine, use of a chlorine removal filter such as the Skuttle WF-10 Filter is suggested. This will aid in the reduction of corrosion caused by high chlorine content.

Specifications

Dimensions...2-13/16"H x 2-13/16"W 2-13/16"D

Current-Sensing Relay A50

- Activates or controls electrically-activated humidifiers, make-up air controls, air cleaners, zone dampers, and more
- Multispeed blower to coordinate operation of the HVAC accessory with the furnace
- Engineered for safety – protective rubber guard separates current-bearing wire from steel bracket; does not invalidate existing equipment warranty



Specifications

Dimensions

2-3/4"W x 1-5/16"H x 1-1/16"D

Technical

24 Volt circuit

Max current load 1 amp

Easy to wire and install



Skuttle Mfg. Co. 101 Margaret Street, Marietta, Ohio 45750

Phone: 888.SKUTTLE | Fax: 740.373.9565 (f) | customerservice@skuttle.com

www.skuttle.com **Made in the U.S.A.**